



BE PART OF THE MISSION

ARCTURUS 5000

FOR SUCCESSFUL
TACTICAL USE



TFX Arcturus 5000

PRODUCT DESCRIPTION

When you have a TFX Arcturus 5000 in hand, you can be in control and safe in the most demanding situations or environments. This extremely powerful tactical flashlight takes performance, functionality and design to a new level. The white-light LED sends an extreme light performance through the reflector, generating maximum brightness and an optimized, tactical light beam exactly where it is needed. The three additional color LEDs (red, green, blue), the removable glass breaker, the silent double front switch and further features make the Arcturus 5000 a versatile and critical tool when facing the dark.

- Tactical highend flashlight made of aluminum for demanding situations or environments
- Tactical light pattern through optimized reflectors for white light and RGB light
- Specific function and feature package: including silent double front switch, Multi Color Strobe, Intelligent Memory, roll protection and glass breaker
- Extreme water protection (IPX8)
- Powerful 2 x 26650 Liion rechargeable batteries; battery and charge status display via 4 separate LEDs

TECHNICAL DATA

Length [mm]	229
Head diameter [mm]	43
Tube diameter [mm]	32
Weight incl. batteries [g]	436
Weight without batteries [g]	243
Focus function	No
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Reflector
Cartridge	No

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	Yes
Total battery voltage [V]	7.2
Total battery capacity [mAh]	5000
Total battery energy ² [Wh]	36
Rechargeable	Yes
Charging time ⁵ [min]	300
Charging technology	Internal
Energy status indicator	Battery Indicator, Charge Indicator

FURTHER SPECIFICATIONS

IP class	IP68
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Mid Power, Power, Strobe

LIGHT SOURCE

Amount LEDs	1
LED type	Xtreme LED
Color	W/R/G/B
Color temperature [K]	5000 to 5500
Color rendering index (CRI)	70

LIGHT VALUES

	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]		5000	1400	120
Beam distance ¹ [m]		230	120	30
Run time ¹ [h]		2	4	35

SWITCH

Front Switch

FEATURES

Red Light, Green Light, Blue Light, Transportation lock , Memory Function



TFX Arcturus 5000

PACKAGING AND LOGISTICS



Exemplary package illustration

PACKAGING INFORMATION

Type of packaging	Box
Scope of delivery	1 set of rechargeable batteries, Hand strap, Pouch, USB cable
Item No.	502558
Customs tariff number	8513100000
Color	black
MSRP price (€)	179.00

SINGLE PACKAGE

Dimensions W x H x D [cm]	14.5 x 31.5 x 8.5
Gross weight [g]	731
GTIN-13	4058205027458

EXPORT CARTON

Unit	12
Dimensions W x D x H [cm]	37 x 34.5 x 48.5
Gross weight [kg]	9.522
GTIN-13	4058205027472



TFX Arcturus 5000

PRODUCT SERIES

TFX - the best tactical flashlights

TFX tactical flashlights combine uncompromising performance with impressive durability, reliability and strong design silhouettes. The illumination power of the TFX allows you to handle every tactical situation one might face at night or in the darkest environment. The TFX lights are specifically designed to provide a massive, concentrated light output and tactically optimized light pattern. They are the right choice for the most demanding situations such as security or defense missions, search and rescue, the outdoors or hunting.

Inspired by the sheer power of nightly stars, the TFX lines of lights carry the names of specific bright celestial bodies: The Zosma line is the entry into the world of tactical TFX flashlights, combining compact dimensions, low weight and a strong light output. The unwavering performance and impressive light output of the Propus models provides confidence when confronting a variety of situations. And finally, the Arcturus is the ultimate high-end flashlight line delivering maximum performance and featuring a multitude of advanced functions (e.g. RGB light) for extreme tactical situations.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

5) Charging time varies by hardware used.

