

3 - PRODUCT DATA SHEET V201111

TFX Propus 1200

PRODUCT DESCRIPTION

Feel confident with a TFX Propus 1200 in your hand for those critical and unexpected situations. Its unwavering performance comes from the extreme light output, uncompromisingly functional design and its impressive robust encasement. Security services, rescue units and police forces can always rely on the Propus 1200 as it is compact and suited for outdoor uses. The newly developed safety strap ensures ideal handling, as does the internally rechargeable, high-performance 18650 battery.

- Powerful yet compact tactical flashlight: optimized light pattern and specific light functions
- End cap switch, glass shield, clip and low weight due to aluminum body
- Extreme water protection (IPX8)
- Adjustable, tactical lanyard
- Powerful 18650 Liion rechargeable battery

TECHNICAL DATA	
Length [mm]	139
Head diameter [mm]	28
Tube diameter [mm]	25
Weight incl. batteries [g]	135
Weight without batteries [g]	85
Focus function	No
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Reflector
Cartridge	No

POWER SUPPLY	\cdot \cdot
Power source type	Rechargoable battery
Battery quantity	
Battery type	Li-ion Li-ion
Battery replaceable	Yes
Total battery voltage [V]	3.63
Total battery capacity [mAh]	3000
Total battery energy ² [Wh]	10.89
Rechargeable	Yes
Charging time ⁵ [min]	210
Charging technology	Internal
Energy status indicator	Charge Indicator
Usable batteries	CR 123 3V,
	Li-ion 3.7V

FURTHER SPECIFICATIONS		
IP class	IP68	
Drop test (drop haight) [m]	2	
Working temperature range [°C]	-20 to +40	

LIGHTFUNCTIONS

Low Power, Mid Power, 20 wer, Strobe

1
Xtreme LED
White
6500 to 7000
70

LIGHT VALUES				
	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]		1200	450	40
Beam distance ¹ [m]		200	120	35
Run time ¹ [h]		2	4.5	32

SWITCH

End Cap Switch

FEATURES

Memory Function

TECHNOLOGIES

Temperature Control System



3 - PRODUCT DATA SHEET

TFX Propus 1200

PACKAGING AND LOGISTICS



To the second se	Exemplary package i
PACKAGING INFOI	Box
Scope of delivery	1 set of rechargeable batteries, Hand strap, Pocket clip, Pouch, USB cable
Item No.	502555
Customs tariff number	85131000000
Color	black
MSRP price (€)	89.90
SINGLE PACKAGE	7.2 × 21 × 8.5
Gross weight [g]	346

SINGLE PACKAGE	
Dimensions W x H x D [cm]	7 2 x 21 x 8.5
Gross weight [g]	346
GTIN-13	4058205027366

EXPORT CARTON	\sim
Unit	24
Dimensions W x D x H [cm]	45.5 x 29 x 34
Gross weight [kg]	9.057
GTIN-13	4058205027380



3 - PRODUCT DATA SHEET v201111

TFX Propus 1200

ACCESORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME	MSRP
Remote Switchs	502583	TFX Remote Switch Type B	19.90 €
Color filter / Signal caps	502585	TFX Color Filter Set 28mm	14.90 €
Fastenings / Brackets	502589	TFX Picatinny Mount Type A	24.90 €
Battery	501001	18650 Li-lon rechargeable Battery 3000 mAh	24.90 €





3 - PRODUCT DATA SHEET v201111

TFX Propus 1200

PACKAGING AND LOGISTICS

TFX - the best tactical flashlights

TFX tactical flashlights combine uncompromising performance with impressive durability, reliability and strong design silhouettes. The illumination power of the TFX allows you to handle every tactical situation one might face at night or in the darkest environment. The TFX lights are specifically designed to provide a massive, concentrated light output and tactically optimized light pattern. They are the right choice for the most demanding situations such as security or defense missions, search and rescue, the outdoors or hunting.

Inspired by the sheer power of nightly stars, the TFX lines of lights carry the names of specific bright celestial bodies: The Zosma line is the entry into the world of tactical TFX flashlights, combining compact dimensions, low weight and a strong light output. The unwavering performance and impressive light output of the Propus models provides confidence when confronting a variety of situations. And finally, the Arcturus is the ultimate high-end flashlight line delivering maximum performance and featuring a multitude of advanced functions (e.g. RGB light) for extreme tactical situations.

INTO NOE

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scape of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

- 1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".
- 2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.
- 5) Charging time varies by hardware used.

