



— PRODUCT DATA SHEET

AL10R Work



AL10R Work

PRODUCT DESCRIPTION

360°, 240° or 120° illumination of large indoor and outdoor worksites has never been easier: Switch the three light panels of our Ledlenser AL10R Work on and off individually to focus on the essential, save energy and reduce light loss.



- Powerful lantern with up to 6300 lm, 5 brightness levels and 5-step tunable white light
- 3 individually switchable light panels for efficient illumination
- Hybrid Power; powerful rechargeable battery as well as mains operation
- High water and dust protection (IP67)
- Flexible mounting via silicone hook and thread for tripod mounting

| TECHNICAL DATA | |
|--------------------------------|---|
| Weight incl. batteries [g] | 1397 |
| Material | Aluminum alloy, PC |
| Product dimensions [mm] | 110 x 390 x 110 |
| POWER SUPPLY | |
| Power source type | 3x 21700 Battery Pack |
| Battery quantity | 1 |
| Rechargeable | Yes |
| Battery type | Lithium-ion |
| Total battery voltage [V] | 10.8 |
| Total battery capacity [mAh] | 4700 |
| Total battery energy [Wh] | 50.76 Wh |
| Battery replaceable | No |
| Charging time [min] | 390 |
| Energy status indicator | Battery Indicator, Charge Indicator, Low Battery Warning, Runtime Indicator |
| FURTHER SPECIFICATIONS | |
| IP class | IP67 |
| Drop test (drop height) [m] | 1.5 |
| Working temperature range [°C] | -20 to +40 |
| Chemical resistance | Alcohol, Break fluid, Coolant, Diesel, Engine oil, Hydraulic oil |
| Robust (IK-Code) | IK07 |

| LIGHT FUNCTIONS | | | | | |
|---|---------------|------|------|------|-----|
| 100%, 75%, 50%, 25%, 10% | | | | | |
| LIGHT SOURCE | | | | | |
| Color | Color tunable | | | | |
| Color temperature [K] | 3000 to 6500 | | | | |
| Color rendering index (CRI) | 80 | | | | |
| LIGHT VALUES | | | | | |
| | 100% | 75% | 50% | 25% | 10% |
| Light output [lm] | 6300 | 5100 | 3600 | 1800 | 750 |
| Beam distance [m] | 60 | 50 | 40 | 30 | 15 |
| Run time [h] | 1 | 1.25 | 2 | 4 | 9.5 |
| SWITCH | | | | | |
| Multifunctional switch | | | | | |
| FEATURES | | | | | |
| Tunable White, Memory Function, Transportation Lock, Chemical Resistant | | | | | |
| TECHNOLOGIES | | | | | |
| Hybrid Power, Temperature Control System, Cooling Technology | | | | | |

AL10R Work

PACKAGING AND LOGISTICS



PACKAGING INFORMATION

| | |
|-------------------|-------------------------------------|
| Type of packaging | Case |
| Scope of delivery | Diffuser, Power Adapter Area Lights |
| Item No. | 502917 |
| Color | Black |
| RRP (€) | 299 |

SINGLE PACKAGE

| | |
|---------------------------|------------------|
| Dimensions W x H x D [cm] | 36.5 x 13.2 x 30 |
| Gross weight [g] | 3920 |
| GTIN-13 | 4058205033268 |

EXPORT CARTON

| | |
|---------------------------|----------------|
| Unit | 2 |
| Dimensions W x H x D [cm] | 39.5 x 34 x 29 |
| Gross weight [g] | 8500 |
| GTIN-13 | 4058205033244 |

AL10R Work

ACCESSORIES

| PRODUCT CATEGORY | ITEM NO. | PRODUCT NAME | PRICE |
|-------------------|----------|----------------------------|---------|
| Chargers & Cables | 503016 | Extension Cable 5 m | 29.90 € |
| Remote Controls | 503018 | Controller for Area Lights | 39.90 € |

PRODUCT SERIES

The Ledlenser Area Lights are for all of you electricians, plumbers, painters, construction workers, craftsmen and DIY enthusiasts: You need to get the job done – and you depend on light. Bright light to illuminate vast work sites. Warm light to stage a project. Homogeneous light for close-range work. Portable light for on the go and stationary light for continuous illumination. Our Area Lights combine all these features to make your job easier.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.